



Slim, compact, space-saving freezer

The 3000 Compact Freezer fits effortlessly into the smallest spaces in your kitchen layout. So you can position it precisely where it suits you. Slim outside, but with plenty of freezer space inside, the compact freezer is the perfect solution to make the most of your available space.

Product Benefits & Features

Just your type - this Compact Freezer fits anywhere

The slim-design Compact Freezer fits easily where you want it. The precise size for when you need a freezer option that doesn't take up too much space.

- 820 mm built-in height
- For fully integrated, door-on-door installation
- Freezer defrosting: manual
- Frostmatic function for rapid freezing
- Fast freeze function with automatic return to normal
- Freezer drawers: 3 Full Width, Transparent Plast
- Freezing tray
- Audible and visual warning signal for high temperature
- Audible and visual warning signal for open door
- Appliance feet: Front adjustable rollers

Manage functions and temperature with Electronic Control

Electronic control gives you the ability to make precise modifications of the temperature and other storage functions. This efficient Upright Freezer also gives you instant feedback of your adjustments on the digital control panel.

Perfectly fresh food with Frostmatic

The Frostmatic function activates the maximum freezing power, so your fresh produce freezes as quickly as possible. The freezer then returns to its normal setting.



Product Specification

Product Number Code	933 027 087	Weight gross cleaner and accessories with packaging	36.51
EAN	7332543788040	Weight net cleaner and accessories no packaging	35.25
EPRELRegCodeE20	385300	Package height	870
ELNE20	F	Package width	630
YearEConsELE20	220	Package depth	620
VN4SE20	95	Country of origin	HU
VN3SE20	0		
NoiseCE20	C		
NoiseIECE20	39		
FrCap1dgtE20	7.1		
RisTE20	13.5		
Height total	819		
ClimE20	SN-N-ST-T		
Width mm	596		
Depth mm	547		
Built in height mm	820		
Built in width mm	600		
Built in depth mm	550		
Main colour	White		
Wheels	Front adjustable rollers		
Connected load (W)	120		
Voltage	230-240		
Required fuse (A)	10		
Frequency	50		
Cord length external	2.4		

